

# Planet ICF-1700



# IP-PHONE Planet ICF-1700



# Firm ware Version

**PLANET**  
Networking & Communication

**Touch Screen Internet Multimedia Phone**  
ICF-1700

### BASIC

STATUS

Network		
MAC Address	00:30:4f:9b:69:ea	
IP Address	192.168.1.7	

Phone Number		
SIP LINE 1	+6621053007@202.129.61.102 :5060	Registered
SIP LINE 2	@ :5060	Unapplied
SIP LINE 3	@ :5060	Unapplied
SIP LINE 4	@ :5060	Unapplied

Firmware Version: 1.0.1057.50.88

Navigation menu: BASIC, NETWORK, VOIP, PHONE, MAINTENANCE, SECURITY, LOGOUT

# การ Config Account cat2call+

The screenshot shows the configuration page for a VOIP account on a PLANET Touch Screen Internet Multimedia Phone. The interface includes a navigation menu on the left and a main configuration area. The 'VOIP' menu item is highlighted. The configuration area is titled 'VOIP' and contains a 'SIP Line' section with a dropdown menu set to 'SIP 1' and a 'Load' button. Below this is a 'Basic Settings' table with various fields for SIP configuration. Two red boxes highlight the 'Status' field, which is 'Registered', and the 'Domain Realm' field, which is 'catnextgen.com'. At the bottom of the configuration area is an 'Advanced Set' button.

**PLANET**  
Networking & Communication

*Touch Screen Internet Multimedia Phone*  
ICF-1700

**VOIP**

SIP | STUN

**SIP Line**

SIP 1 Load

**Basic Settings**

Status	Registered	Domain Realm	catnextgen.com
Server Address	202.129.61.102	Proxy Server Address	
Server Port	5060	Proxy Server Port	
Account Name	6621053007@catnextgen.com	Proxy Username	
Password	*****	Proxy Password	
Phone Number	+6621053007	Backup Server Address	
Display Name	021053007	Backup Server Port	
Enable Registration	<input checked="" type="checkbox"/>	Server Name	

Advanced Set

# การ Config Account cat2call+ Advance set

Advanced Set

### Advanced SIP Settings

Signal Encryption	<input type="checkbox"/>	Enable Session Timer	<input type="checkbox"/>
Signal Key		Session Timeout	0 seconds
RTP Encryption	<input type="checkbox"/>	Conference Type	Local
Media Key		Conference Number	
Enable BLF List	<input type="checkbox"/>	Subscribe For MWI	<input type="checkbox"/>
BLF List Number		MWI Number	
NAT Keep Alive	<input checked="" type="checkbox"/>	Subscribe Period	300 seconds
NAT Keep Alive Period	55 seconds	Registration Expire	60 seconds
User Agent	ICF-1700	Server Type	COMMON
DTMF Type	DTMF_RFC2833	RFC Protocol Edition	RFC3261
Local Port	5060	Transport Protocol	UDP
RFC Privacy Edition	None	Keep Authentication	<input type="checkbox"/>
Enable Via rport	<input type="checkbox"/>	Click To Talk	<input type="checkbox"/>
Enable PRACK	<input checked="" type="checkbox"/>	Answer With A Single Codec	<input checked="" type="checkbox"/>
Long Contact	<input type="checkbox"/>	Auto TCP	<input type="checkbox"/>
URI Conversion	<input type="checkbox"/>	Enable Strict Proxy	<input type="checkbox"/>
Dial Without Register	<input type="checkbox"/>	Enable GRUU	<input type="checkbox"/>
Ban Anonymous Call	<input type="checkbox"/>	Enable Displayname Quote	<input type="checkbox"/>
Enable DNS SRV	<input type="checkbox"/>	Enable user=phone	<input checked="" type="checkbox"/>

Apply

# Config codec voice&video

**PHONE**

MEDIA FEATURE

### Voice Configuration

First Codec	G729	Second Codec	G711Alaw64k
Third Codec	G723	Fourth Codec	None
Fifth Codec	None	Sixth Codec	None
Seventh Codec	None	Eighth Codec	None
Signal Standard	China	DTMF Payload Type	101
ILBC Payload Type	97 (96~127)	ILBC Payload Length	20ms
AMR Payload Type	108 (96~127)	AMR-WB Payload Type	109 (96~127)
G723 Bit Rate	6.3kb/s	G729 Payload Length	20ms
Hook Check	Normal	VAD	<input type="checkbox"/>

Apply

### Video Configuration

First Video Codec	H.264	Second Video Codec	H.263
Third Video Codec	None	Video Packet Size	1200 Bytes
H.264 Payload Type	117 (96~127)	Mpeg4 Payload Type	125 (96~127)
Video Bit Rate	768kbps	Video Frame Rate	30fps
Video Resolution	CIF(352*288)		

**BASIC**  
**NETWORK**  
**VOIP**  
**PHONE**  
**MAINTENANCE**  
**SECURITY**  
**LOGOUT**