

Fanvil PA2



Fanvil PA2

SIP Basic Settings

Line SIP 1

Default fix ip
<http://192.168.1.128>
 user = admin , password admin

Basic Settings >>

Line Status	Registered	SIP Proxy Server Address	catnextgen.com
Phone number	+6621079443	SIP Proxy Server Port	5060
Display name	+6621079443	Backup Proxy Server Address	
Authentication Name	6621079443@catnextgen.	Backup Proxy Server Port	5060
Authentication Password	*****	Outbound proxy address	202.129.61.102
Activate	<input checked="" type="checkbox"/>	Outbound proxy port	
		Realm	catnextgen.com

Codecs Settings >>

Advanced Settings >>

Apply

Fanvil PA2

Information Account Configurations Upgrade Auto Provision FDMS Tools

System

System Information

Model:	PA2
Hardware:	2.1
Software:	2.1.1.2924
Uptime:	03 : 57 : 20
Last uptime:	00:00:00
MEMInfo:	ROM: 0.8/8(M) RAM: 2.2/16(M)
System Time:	2018-10-29 16:33

Network

Network mode:	Static IP
MAC:	0c:38:3e:1f:bd:13
IP:	192.168.1.128
Subnet mask:	255.255.255.0
Default gateway:	192.168.1.1

SIP Accounts

Line 1	+6621079443	Registered
Line 2	N/A	Inactive

> System

> Network

> Line

> Intercom settings

> Security settings

> Function Key

Line SIP 1 ▼

Basic Settings >>

Codecs Settings >>

Disabled Codecs

G.711U
G.722
G.723.1
G.726-32

Enabled Codecs

G.711A
G.729AB

Advanced Settings >>

Apply